GENERALSCAN

GS R3521 Ruglove Barcode Scanner

Metal frame structure

With this delicate design, the PCBA is protected from drops and bumps due to the metal protective frame, which ensures reliable operation. Passed the 1 meter 20,000 times rolling test, the performance is reliable.

Shell material is Hard

The hardness of shell(ABS+PC material) has been greatly improved, is impact-resistant, tensile-resistant, and meets enterprise-grade standards. The imager window(acrylic material) has high strength and strong light transmission.

Scan engin, Zebra SE4107

Bright, rectangular illumination field and LED aiming spot makes scanning more fast and easy. White illumination easily captures color barcodes.

Long battery life

600mAh large-capacity battery, up to 14 hours of use. The battery can be replaced quickly, and it is equipped with dual-charge and multi-charge chargers. Up to 16 batteries can be charged at the same time to ensure continuous work in multiple shifts.

Ruglove Wear

Ergonomically designed, it is still comfortable to wear for a long time. With Ruglove, workers can choose and decide to use left or right hand to work and swap scanning hands on the fly.

Wide applicability

High-quality scanning for printed and mobile barcodes. It can capture virtually any barcode printed on paper labels or displayed on mobile phones. Support HID, SPP, BLE three transmission protocols. Support two modes of classic bluetooth and low energy bluetooth. USB mode supports keyboard and virtual serial port, adapting to various application interfaces.

Application fields

The scanner can be widely used in manufacturing, warehousing, logistics, retail and express transportation, and has incomparable advantages in improving production efficiency and accuracy.

ACCESSORIES



Armband AB1800



Silicone Glove+Trigger



Bluetooth Dongle GDA201



Battery Charger

GS GCR201(Dual-slot)



Battery charger GS GCR202(8-slot)/203(16-slot)

PRODUCT SPEC SHEET

Wearable Barcode Scanner GS R3521

PERFORMANCE CHARACTERISTICS

1280 x 960 pixels

Skew tolerance: ±60° from normal Pitch tolerance: ±60° from normal Roll tolerance: 360° from normal

1D: Code39, Code128, Codabar, Code11, UPC/EAN, Interleaved

2D: PDF417, Postal CodesMicro PDF, Micro PDF417, Code128 Emulation, Aztec, Data Matrix, GS1 Data Matrix, QR Code, GS1

of 5, GS1 Databar, Code93, MSI, Composite

QR, Maxicode, Micro QR, Han Xin, Grid Matrix

Support storage of 3839 EAN-13 barcodes

2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix 2 of 5, Korean 3

Rolling shutter 2D CMOS Image

White LED Green LED

USB, Bluetooth

PHYSICAL PARAMETER

Scanner Dimensions	64.8mm(L) × 34.6mm(W) × 24.8mm(D)	
Scanner Weight	39.2g(Scanner body)	
Battery Capacity	600mAh	
Charging	5V1A	
Charging Time	120min	
Battery Life	12.9h(scan every 5 seconds)	
Notification	LED, Buzzer, Vibration	

USB	
USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

USER ENVIRONMENT Max 107639lux (direct sunlight) Ambient Light

Operating Temperature	-10°C~50°C
Storage Temperature	-10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M
	with frequency of 10 times per minute.
Electrostatic	±8kv DC discharge, ±15kv air discharge
Discharge (ESD)	
Certificates	CE, FCC, KC, TELEC, ROHS, ANATEL, NOM, EAC

SOFTWARE SUPPORT

Generalscan Keyboard Pro, Generalscan SDK Demo, Generalscan OTA Tools, Generalscan iCode, G-Service

DECODE RANGES				
5 mil Code 39	61.0 - 241.0MM			
5 mil Code 128	71.0 - 229.0MM			
6.6 milPDF417	61.0 - 203.0MM			
10 mil DataMatrix	74.0 - 216.0MM			
100% UPC-A	46.0 - 495.0MM			
15 mil QR Code	30.0 - 292.0MM			
20 mil QR Code	30.0 - 356.0MM			



Optical Resolution

Skew, Pitch & Roll

Illumination

Supported

Interface

Offline Mode

Symbologies

Aiming

Shutter

Sensor

Bluetooth Protocol	HID Keyboard, SPP, and BLE	
Bluetooth Range	Communication distance connected to mobile phone	
	164.04ft./50m (without obstructions)	
Bluetooth OTA	Bluetooth OTA	



Generalscan Inc.

() 200 Buckelew Ave, Jamesburg, NJ 08831, USA

+1 732 895 6821

Heinsberg Germany

Generalscan LLC

- (Calle San Luis Potosi 51, Roma Norte 06700, Ciudad de México
- +52 5552727861

GENERALSCAN ELEKTRONIK VE TEKNOLOJI SAN. VE TIC. LTD. ŞTİ.

- SI FSM Mah. Siir Sk. Relux Plaza No 10, Ümraniye 34764, Istanbul, Turkey
- +90 542 478 5873

- **Generalscan Electronics GmbH**

() Hochstraße 42, 52525

🗘 +49 1516 7161256

