

GS R5524 Ruglove MK III Barcode Scanner



Ready to Go Straight Out of the Box

Workers can visualize how to wear the MK III glove without any special training. The wrist and index finger straps are adjustable, so the MK III fits virtually any hand size, eliminating the needs to order different sized gloves or manage multiple gloves.

Comfortable Wear Guaranteed with Lightweight Materials

Utilizing lightweight materials and an ergonomic design, the MK III glove guarantees lasting comfort even during extended daily wear, effectively minimizing user fatigue and enhancing overall comfort levels.

Optimized ROI via Versatile Replaceable Components

All parts of the Ruglove Mark III scanner, including the removable batteries, triggers, and gloves, are interchangeable and can be used with all Generalscan scanners. This interchangeability not only reduces replacement expenses but also optimizes the return on investment for users.

Scan Engine, Zebra SE5500

Highly visible green laser aimer. The engine SE5500 includes an innovative wide aim pattern green laser aimer with a wide targeting pattern that's up to 7x more visible than a red aimer dot. GS R5524 has an extraordinary working range — from 5.6 cm to over 40 ft./7.2 m when scan barcode DataMatrix of 100mil.

Lightweight Industrial Scanner for Inventory Checking

Due to its lightweight design, users can easily carry and use it, making it an ideal choice for mobile work scenarios. Whether in warehouses, production lines, or retail environments, users can conveniently carry and use this scanner.

ACCESSORIES



Bluetooth Dongle
GS GDA201



Battery Charger
GS GCR202(8-slot)/203(16-slot)



Battery Charger
GS GCR201(Dual-Slot)



Armband
(AB1800)



Ruglove MK III + Trigger

PRODUCT SPECIFICATION

Wearable Barcode Scanner GS R5524

PHYSICAL PARAMETER

Dimensions	2.76in.(L) x 1.43in.(W) x 1.06in.(H) 70.00mm(L) x 36.00mm(W) x 26.80mm(H)
Weight	37.5g(Scanner body)
Battery Capacity	600mAh
Charging	5V ---1A
Charging Time	120min
Battery Life	6.9h(scan every 5 seconds, 10 centimeter reading) 4h(scan every 5 seconde, 1 meter reading)
Notification	LED, Buzzer, Vibration

PERFORMANCE CHARACTERISTICS

Optical Resolution	2688 x 1520 pixels
Shutter Type	Global shutter
Sensor	2D CMOS Image
Skew, Pitch & Roll	Skew tolerance: $\pm 60^\circ$ from normal Pitch tolerance: $\pm 60^\circ$ from normal Roll tolerance: 360° from normal
Field of View	Horizontal 37° , Vertical 21.4°
Illumination	White LED
Aiming	Green Laser
Supported Symbolologies	1D: Code39, Code128, Codabar, Code11, UPC/EAN, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix 2 of 5, Korean 3 of 5, GS1 Databar, Code93, MSI, Composite 2D: PDF417, Postal CodesMicro PDF, Micro PDF417, Code128 Emulation, Aztec, Data Matrix, GS1 Data Matrix, QR Code, GS1 QR, Maxicode, Micro QR, Han Xin, Grid Matrix, DotCode, OCR
Network Connections	USB, Bluetooth
Offline Mode	Support storage of 3839 EAN-13 barcodes

BLUETOOTH

Bluetooth Protocol	HID Keyboard, SPP, and BLE
Bluetooth Range	Communication distance connected to mobile phone > 164.04ft./50m (without obstructions)
Bluetooth OTA	Bluetooth OTA

USB

USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

USER ENVIRONMENT

Ambient Light	Max 107,639lux (direct sunlight)
Operating Temperature	14°F ~ 122°F / -10°C~50°C
Storage Temperature	14°F ~ 122°F / -10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M with frequency of 10 times per minutes.
Electrostatic Discharge (ESD)	± 8 kv dc discharge, ± 15 kv air discharge
Certificates	CE, FCC, KC, TELEC, RoHS, ANATEL, NOM, EAC

SOFTWARE SUPPORT

Generalscan Keyboard Pro, Generalscan SDK Demo, Generalscan OTA Tools, Generalscan iCode, G-Service

DECODE RANGES

Note: Printing resolution, contrast and ambient light dependent

3 mil Code 39	69.0 - 411.0MM
5 mil Code 39	64.0 - 676.0MM
5 mil PDF417	71.0 - 498.0MM
6.67 mil PDF417	66.0 - 650.0MM
10 mil DataMatrix	56.0 - 688.0MM
13 mil 100% UPCA	64.0 - 1800.0MM
15mil Code 128	182.0 - 1829.0MM
20mil Code 39	FOV limited - 2769.0MM
55 mil Code 39	FOV limited - 7442.0MM
100 mil Code 39	FOV limited - 14072.0MM
100 mil DataMatrix	FOV limited - 6858.0MM

GENERALSCAN

Generalscan Inc.

200 Buckelew Ave, Jamesburg,
NJ 08831, USA
+1 732 895 6821

Generalscan Electronics GmbH

Hochstraße 42, 52525
Heinsberg Germany
+49 1516 7161256

Generalscan LLC

Calle San Luis Potosi 51,
Roma Norte 06700,
Ciudad de México
+52 5552727861

GENERALSCAN ELEKTRONIK VE TEKNOLOJİ SAN. VE TİC. LTD. ŞTİ.

FSM Mah. Siir Sk. Relux Plaza No 10,
Ümraniye 34764,
İstanbul, Turkey
+90 542 478 5873