

WT3521 Wearable Armband Ring Scanner



A Selection of Three Armbands Suited to Various Work Settings

Three distinct types of armbands are on offer, boasting individual characteristics and designs to cater to diverse preferences and requirements. Whether you find yourself in a demanding warehouse environment, a streamlined production setting, or a dynamic retail space, there's an armband tailored precisely to your needs.

Stable Armband AB1800 - The Silicone Strap on AB1800 is Adjustable to Fit a Variety of Mobile Terminals

The silicone strap of AB1800 makes it suitable for securing a variety of mobile terminals. The silicone material fits securely around smartphones or other mobile devices of all sizes, ensuring fit and stability and preventing slippage during movement. The AB1800 armband's ability to adapt to different sizes of mobile devices makes it a practical accessory for those who use different devices or wish to change to a different device.

With Zebra SE4107 Engine, the Bright, Rectangular Illumination Field and Green LED Aiming Spot Enable Accurate Aiming for Exceptional Ease of Use

White illumination increases scanning flexibility by enabling the easy capture of any color barcode, with the megapixel sensor, wide field of view and broad 20 in./50.8cm working range, barcode capture is faster and easier than ever.

Wired Way Ensures Instant Connection

The Type-C cable that connects the scanner to the mobile terminal provides secure and stable data transmission, reducing the chance of data interruption or connection problems. In addition, the Type-C connector, which is designed with a reversible plug so that you don't have to worry about the direction of insertion, supports high-speed data transfer and enables fast transmission.

PRODUCT SPEC SHEET

Wearable Armband Ring Scanner WT3521

PHYSICAL PARAMETER

Scanner Dimensions	64.8mm(L) × 34.6mm(W) × 24.8mm(D)
Scanner Weight	39.2g(Scanner body)
Notification	LED, Buzzer, Vibration

INTERFACE

USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

ARMBAND PARAMETER

Armband Type	AB1800, AB2000, AB2200
Strap Length	Adjustable, 27cm and 38cm are available for AB2200
Armband Direction	360° rotatable

USER ENVIRONMENT

Ambient Light	Max 107639lux (direct sunlight)
Operating Temperature	-10°C~50°C
Storage Temperature	-10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M
	with frequency of 10 times per minute.
Electrostatic	±8kv dc discharge, ±15kv air discharge
Discharge (ESD)	
Certificates	ROHS, NOM, EAC

PERFORMANCE CHARACTERISTICS

Optical Resolution		1280 x 960 pixels
Shutter		Rolling shutter
Sensor		2D CMOS Image
Skew, Pitch & Roll		Skew tolerance: ±60° from normal
		Pitch tolerance: ±60° from normal
		Roll tolerance: 360° from normal
Illumination		White LED
Aiming		Green LED
Supported	1D:	Code39, Code128, Codabar, Code11, UPC/EAN, Interleaved
Symbologies		$2\ \text{of}\ 5$, Discrete $2\ \text{of}\ 5$, Chinese $2\ \text{of}\ 5$, Matrix $2\ \text{of}\ 5$, Korean 3
		of 5, GS1 Databar, Code93, MSI, Composite
	2D:	PDF417, Postal CodesMicro PDF, Micro PDF417, Code128
		Emulation, Aztec, Data Matrix, GS1 Data Matrix, QR Code, GS1
		QR, Maxicode, Micro QR, Han Xin, Grid Matrix
Interface		USB
Offline Mode		Support storage of 4388 EAN-13 barcodes

DECODE RANGES

5 mil Code 39	61.0 - 241.0MM
5 mil Code 128	71.0 - 229.0MM
6.6 milPDF417	61.0 - 203.0MM
10 mil DataMatrix	74.0 - 216.0MM
100% UPC-A	46.0 - 495.0MM
15 mil QR Code	30.0 - 292.0MM
20 mil QR Code	30.0 - 356.0MM







AB2200

GENERALSCAN

Generalscan Inc.

- 200 Buckelew Ave, Jamesburg, NJ 08831, USA
- +17328956821

Generalscan Electronics GmbH

- (P) Hochstraße 42, 52525 Heinsberg Germany
- +49 1516 7161256

Generalscan LLC

- Calle San Luis Potosi 51, Roma Norte 06700, Ciudad de México
- +52 5552727861

GENERALSCAN ELEKTRONIK VE TEKNOLOJI SAN. VE TIC. LTD. ŞTİ.

- FSM Mah. Siir Sk. Relux Plaza No 10, Ümraniye 34764, Istanbul, Turkey
- +90 542 478 5873