

GS R3520 Handheld Barcode Scanner

All day comfort that workers can count on

The ergonomic designed grip provides maximum comfort, even in the heavy duty scanning environments, which reduced greatly user fatigue and increased productivity.

The Flexgrip is easy to assemble and clean

It is very easy to assemble on the scanner, just press and release the latch it will be fixed. Because of the small size, it is also very easy to clean.

Triggers built for intensive scanning

The triggers are rated for millions of pressing — instead of the typical few hundred thousand trigger presses. It is obvious that the frequency of replacing triggers getting lower, and also the cost.



Scan engine, Zebra SE2707

High-quality scanning for printed and mobile barcodes. It captures virtually any barcode printed on paper labels or displayed on mobile phones. With bright, rectangular illumination field and LED aiming spot, users instantly know if they are aiming at the right spot for exceptional ease of use.



NFC pairing saves at least half of the connection time

Using the NFC makes the Bluetooth connection more convenient and faster. User can simply tap the scanner with any NFC-enabled devices. No need to open the bluetooth settings to identify and select the device.

Maximum replaceable parts bring minimize downtime

The removable and swappable scanner body and battery minimize the entire time of reassembly process. Furthermore, the one-second swappable battery makes sure scanners have virtually no downtime. There is no need to worry about dead battery to influence your daily working any more.

ACCESSORIES



Bluetooth Dongle
(GDA201)



Battery Charger
GS GCR208(8-slot) /203(16-slot)



Battery Charger
Dual-Slot Battery Charger



Armband
(AB1800)



Flexgrip
(GS GHR201)

PRODUCT SPEC SHEET

Handheld Barcode Scanner GS R3520

PHYSICAL PARAMETER

Scanner Dimensions	64.8MM(H) × 34.6MM(W) × 24.8MM(D)
Scanner Weight	30.2g (scan body)
Handle Dimensions	166.5MM(H) × 48.7MM(W) × 75.8MM(D)
Handle Weight	144.5g
Battery Capacity	600mAh
Charging	5V⎓1A
Charging Time	120min
Battery Life	14.3 hours (scan every 5 seconds)
Notification	LED, Buzzer, Vibration

PERFORMANCE CHARACTERISTICS

Optical Resolution	600 x400 pixels
Shutter	Rolling shutter
Sensor	2D CMOS Image
Skew, Pitch & Roll	Skew tolerance: ±60° from normal Pitch tolerance: ±60° from normal Roll tolerance: 360° from normal
Field of View	Horizontal 42°, Vertical 28°
Illumination	Red LED
Aiming	Red Led
Supported Symbologies	1D: Code39, Code128, Codabar, Code11, UPC/EAN, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix 2 of 5, Korean 3 of 5, GS1 Databar, Code93, MSI, Composite 2D: PDF417, Postal Codes, Micro PDF, Micro PDF417, Code128 Emulation, Aztec, Data Matrix, GS1 Data Matrix, QR Code, GS1 QR, Maxicode, Micro QR, Han Xin, Grid Matrix, Dot-Code, OCR
Interface	USB, Bluetooth
Offline Mode	Support storage of 4388 EAN-13 barcodes

BLUETOOTH

Bluetooth Protocol	HID Keyboard, SPP, and BLE
Bluetooth Range	Communication distance connected to mobile phone > 164.04ft./50m (without obstructions)
Bluetooth OTA	Bluetooth OTA

USER ENVIRONMENT

Ambient Light	Max 107639lux (direct sunlight)
Operating Temperature	-10°C~50°C
Storage Temperature	-10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M with frequency of 10 times per minutes.
Electrostatic Discharge (ESD)	±8kv DC discharge, ±15kv air discharge
Certificates	CE, FCC, KC, TELEC, RoHS, ANATEL, NOM, EAC

SOFTWARE SUPPORT

Generalscan Keyboard Pro, Generalscan SDK Demo, Generalscan OTA Tools, Generalscan iCode, G-Service

DECODE RANGES

5 mil Code 39	51.0MM - 16.2 MM
5 mil Code 128	63.0MM - 127.0MM
6.6 mil PDF417	63.0MM - 160.0MM
10 mil PDF417	45.0MM - 228.0MM
13 mil 100% UPCA	50.0MM - 317.0MM
20 mil Code39	50.0MM - 495.0MM
20 mil DataMatrix	38.0MM - 343.0MM
20 mil QR Code	38.0MM - 279.0MM

GENERALSCAN

Generalscan Inc.

📍 20 Kulick Road Fairfield,
New Jersey, 07004, USA
☎ +1 888 633 7931
✉ sales@generalscan.cloud

Generalscan Electronics GmbH

📍 Hochstraße 42, 52525
Heinsberg Germany
☎ +49 1516 7161256

Generalscan LLC

📍 Calle San Luis Potosi 51,
Roma Norte 06700,
Ciudad de México
☎ +52 5552727861

GENERALSCAN ELEKTRONIK VE TEKNOLOJİ SAN. VE TIC. LTD. ŞTİ.

📍 FSM Mah. Siir Sk. Relux Plaza No 10,
Ümraniye 34764,
İstanbul, Turkey
☎ +90 542 478 5873