

GS R5522 Ruglove Barcode Scanner

Rugged internal structure owes to protecting PCBA with aluminum alloy frame

With this delicate design, the PCBA is protected from drops and bumps due to the metal protective frame, which ensures reliable operation.

Robust external structure with enhanced hardness of body and imager window

The hardness of shell and imager window has been greatly improved, which contributes to the enterprise-class ruggedness and durability.

Scan engine, Zebra SE4750MR

Data capture capabilities of it is comprehensive. It can capture 1D and 2D barcodes in milliseconds, from high resolution photos, to letter, legal, A4 and A5 documents that are fully searchable and editable. There is no need to ever align the bar code and imager for highly intuitive and rapid bar code capture.

Suitable for medium and long-Range Scanning

GS R5522 decodes barcode Code 39 of 100mil 4369MM away, and barcode 100% UPC-A 965MM away.

Comfortable wearing style

The design of Ruglove conforms to ergonomics, which makes workers work at ease, even wearing for long time, and no need to worry about the spreading of germs.

The rapidly-replaced battery minimizes the downtime

600mAh battery provides a longer battery lifecycle and ensures uninterrupted full-shift operation. The feature of swappable helps to increase the productivity during receiving, inventorying, picking, sorting, packing, etc.

Maximum ROI with multiple replaceable parts

The removable and swappable battery and trigger assemblies and retractable lanyard compatible with all the Generalscan scanner bodies, Maximizing return on investment.

Featured with Zebra's latest decoder - PL5000

The image sensor array in the imager engine captures an image of the barcode through the engine's optical lens. The engine automatically adjusts illumination, exposure, and other parameters to obtain the best quality image.

Application fields

GS R5522 can be used widely in manufacturing, warehousing, logistics, retail, and transportations industries. It has incomparable advantages in improving quality and accuracy.



ACCESSORIES



Armband
AB1800



Silicone Glove+ Trigger



Lycra Glove+ Trigger



Bluetooth Dongle
GDA201



Battery Charger
GS GCR201 (Dual-slot)



Battery charger
GS GCR202 (8-slot)/203 (16-slot)

PRODUCT SPEC SHEET

Wearable Barcode Scanner GS R5522

PHYSICAL PARAMETER

Scanner Dimensions	2.76in.(L) x 1.43in.(W) x 1.06in.(H) 70.00mm(L) x 36.00mm(W) x 26.80mm(H)
Scanner Weight	40.7g (scanner body)
Battery Capacity	600mAh
Charging	5V---1A
Charging Time	120min.
Battery Life	9.0h (to be triggered every 5 seconds)
Notification	LED, Buzzer, Vibration

PERFORMANCE CHARACTERISTICS

Optical Resolution	1280 x 960
Shutter	Global shutter
Sensor	2D CMOS Image
Skew, Pitch & Roll	Skew tolerance: $\pm 60^\circ$ from normal Pitch tolerance: $\pm 60^\circ$ from normal Roll tolerance: 360° from normal
Field of View	Horizontal 31° , Vertical 23°
Illumination	White LEDx2
Aiming	Red Laser
Supported	1D: Code39, Code128, Codabar, Code11, UPC/EAN, Interleaved
Symbologies	2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix 2 of 5, Korean 3 of 5, GS1 Databar, Code93, MSI, Composite 2D: PDF417, Postal CodesMicro PDF, Micro PDF417, Code128 Emulation, Aztec, Data Matrix, GS1 Data Matrix, QR Code, GS1 QR, Maxicode, Micro QR, Han Xin, Grid Matrix, DotCode, OCR
Interface	Scanner: USB, Bluetooth
Offline Mode	Support storage of 4388 EAN-13 barcodes

BLUETOOTH

Bluetooth Protocol	HID Keyboard, SPP, and BLE
Bluetooth Range	Communication distance connected to mobile phone > 164.04ft./50m (without obstructions)
Bluetooth OTA	Bluetooth OTA

USB

USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

USER ENVIRONMENT

Ambient Light	Max 107,639 lux (direct sunlight)
Operating Temperature	14°F ~ 122°F / -10°C~50°C
Storage Temperature	14°F ~ 122°F / -10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M with frequency of 10 times per minutes.
IP Level of Glove	Washable
Electrostatic	± 8 kv DC discharge, ± 15 kv air discharge
Discharge (ESD)	
Certificates	CE, FCC, KC, TELEC, RoHS, ANATEL, NOM, EAC

DECODE RANGES

5 mil Code 128	2.1in. - 54.0in. /53mm -1372mm
5 mil PDF417	7.4in. - 16.0in. /188mm - 406mm
7.5 mil DataMatrix	4.0in. - 40.0in. /102mm - 1016mm
10 mil DataMatrix	8.1in. - 13.1in. /206mm - 333mm
13mil UPC-A	8.3in. - 12.8in. /211mm - 325mm
15 mil Code 128	7.0in. - 17.0in. /178mm - 432mm
20mil Code 39	11.5in. - 138.0in. /292mm - 3505mm
100 mil Code 39	2.3in. - 38.0in. /58mm - 965mm
160 mil DataMatrix	11.0in. - 172in. /279mm - 4369mm
20 mil QR Code	2.8in. - 26.6in. /71mm - 676mm

GENERALSCAN

Generalscan Inc.

200 Buckelew Ave, Jamesburg,
NJ 08831, USA
+1 732 895 6821

Generalscan Electronics GmbH

Hochstraße 42, 52525
Heinsberg Germany
+49 1516 7161256

Generalscan LLC

Calle San Luis Potosi 51,
Roma Norte 06700,
Ciudad de México
+52 5552727861

GENERALSCAN ELEKTRONIK VE TEKNOLOJİ SAN. VE TİC. LTD. ŞTİ.

FSM Mah. Siir Sk. Relux Plaza No 10,
Ümraniye 34764,
İstanbul, Turkey
+90 542 478 5873