

# GS R3521 Ruglove - MK2 Bluetooth Wearable Scanner

# Scan engine, Zebra SE4107

Easy intuitive first-time aiming, the bright, rectangular illumination field and green LED aiming spot enables accurate aiming for exceptional ease of use. White illumination increases scanning flexibility by enabling the easy capture barcodes of any color.

# A glove with the feature of easy-to-clean and many-time-clean

The MK2 glove is easy-to-clean mostly due to easily removable scanner body, which contributes more on improving the hygiene and preventing the spread of germs. Workers always have a clean glove even if this set of scanners is in all-day, every-day use.

# Comfortable microfiber glove

The glove of MK2 made of microfiber, which is soft but not easy to deform, and is scratch resistant with high tensile strength. Working in harsh environments is no longer a problem.

# Durable and Rugged for All-Day, Every-Day Use

GS R3521 is dual-tested for durability-drop and tumble. Multiple drop it on concrete from 4.9ft./1.5M, tumble it from 3.3ft./1M with frequency of 10 times per minutes for 20,000 times, GS R3521 is engineered for durability and uptime.



# Press slightly with one hand to scan, enhanced working efficiency greatly

With a slight press, the glove wear well, and ready to scan. In this way, workers do not need training on how to use it any more. Working efficiency improved greatly by easy operating and instant set-up.

#### Unmatched advanced range scanning

GS R3521 offers best-in-class scanning performance and scanning range. It reads 100% UPC-A barcodes from the near of 46mm to the far of 495mm – the widest working range in this class.

# Maximum replaceable parts bring minimize downtime

The removable and swappable sanner body and battery minimize the entire time of reassembly process. Furthermore, the one-second swappable battery makes sure scanners have virtually no downtime. There is no need to worry about dead battery to influence your daily working any more.

#### **ACCESSORIES**



Glove MK2 + Trigger



Armband AB1800



Bluetooth Dongle GDR201



Battery Charger
Dual-slot GS GCR201



Battery charger GS GCR202(eight-slot)/203(sixteen-slot)

# **PRODUCT SPEC SHEET**

GS R3521 Ruglove-MK2 Bluetooth Wearable Scanner

# **PHYSICAL PARAMETER**

Scanner Dimensions	64.8(L) × 34.6(W) × 24.8(D)mm
Scanner Weight	29.5g (scan body)
Glove Dimensions	260(L)×120(W)×2.5(D)mm
Glove Weight	21.2g
Material of Glove	Microfiber
Battery Capacity	600mAh
Charging	5V1A
Charging Time	120min
Battery Life	10.6 hours (scan every 5 seconds)
Notification	LED, Buzzer, Vibration

# PERFORMANCE CHARACTERISTICS

1200 v 060 pivolo
1280 x 960 pixels
Rolling shutter
2D CMOS Image
Skew tolerance: ±60° from normal
Pitch tolerance: ±60° from normal
Roll tolerance: 360° from normal
Horizontal 44.5°, Vertical 33.5°
White LED
Green LED
1D: Code39, Code128, Codabar, Code11, UPC/EAN,
Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix 2 of
5, Korean 3 of 5, GS1 Databar, Code93, MSI, Composite
2D: PDF417, Postal CodesMicro PDF, Micro PDF417, Code128
Emulation, Aztec, Data Matrix, GS1 Data Matrix, QR Code,
GS1 QR, Maxicode, Micro QR, Han Xin, Grid Matrix,
DotCode, OCR
USB, Bluetooth;
Support storage of 3839 EAN-13 barcodes

# **BLUETOOTH**

Bluetooth Protocol	HID Keyboard, SPP, and BLE
Bluetooth Range	Communication distance connected to mobile phone $>$
	164.04ft./50m (without obstructions)
Bluetooth OTA	Bluetooth OTA

# TRIGGER METHOD

Trigger	By the key on glove surface
---------	-----------------------------

#### **USB**

USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

#### **USER ENVIRONMENT**

Ambient Light	Max 107639lux (direct sunlight)
Operating Temperature	-10°C~50°C
Storage Temperature	-10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M
	with frequency of 10 times per minutes.
IP Level of Glove	Washable
Electrostatic	±8kv DC discharge, ±15kv air discharge
Discharge (ESD)	
Certificates	CE, FCC, KC, TELEC, RoHS, ANATEL, NOM, EAC

#### **SOFTWARE SUPPORT**

Generalscan Keyboard Pro, Generalscan SDK Demo, Generalscan OTA Tools, Generalscan iCode, G-Service

# **DECODE RANGES**

5 mil Code 39	61 MM - 241 MM	
5 mil Code 128	71 MM - 229 MM	
6.67 milPDF417	61 MM - 203 MM	
10 mil DataMatrix	74 MM - 216 MM	
100% UPC-A	46 MM - 495 MM	
15 mil QR Code	30 MM - 292 MM	
20 mil QR Code	30 MM - 356 MM	

# **GENERALSCAN**

#### Generalscan Inc.

200 Buckelew Ave, Jamesburg, NJ 08831, USA

+1 732 895 6821

# Generalscan Electronics GmbH

(P) Hochstraße 42, 52525 Heinsberg Germany

+49 1516 7161256

# Generalscan LLC

Calle San Luis Potosi 51,
 Roma Norte 06700,
 Ciudad de México

+52 5552727861

# GENERALSCAN ELEKTRONIK VE TEKNOLOJI SAN. VE TIC. LTD. ŞTİ.

FSM Mah. Siir Sk. Relux Plaza No 10, Ümraniye 34764, Istanbul, Turkey

+90 542 478 5873