

WT5524 Wearable Armband Glove Scanner



Easy-to-Wear Armband AB2000 - Slightly Stick It on and You're Ready to Go!

AB2000 is designed for effortless wearability, allowing users to quickly and easily attach it by simply sticking it on. By requiring minimal effort to put on, the AB2000 enables users to get ready swiftly for their activities without any complicated adjustments. This enhances user convenience, ensuring that users can seamlessly incorporate it into their daily routines without any unnecessary complications.

A Selection of Three Armbands Suited to Various Work Settings

Three distinct types of armbands are on offer, boasting individual characteristics and designs to cater to diverse preferences and requirements. Whether you find yourself in a demanding warehouse environment, a streamlined production setting, or a dynamic retail space, there's an armband tailored precisely to your needs.

Plug-and-Play, No Bluetooth Pairing Process

The Type-C cable secures a dependable and steady link between the scanner and your mobile device, reducing the chances of data interruptions or connectivity glitches. Featuring a reversible plug setup, the Type-C connector streamlines the insertion procedure, ensuring effortless connections and enabling high-speed data transfers for quick and effective communication.

360° Rotatable Armband - Supports Landscape and Vertical Viewing

With a 360° rotatable mechanism, the armbands allow users to adjust their mobile device to either landscape or vertical orientation easily. This feature provides users with the flexibility to choose their preferred viewing mode based on their activities, content, or personal preference. Users can switch to landscape mode for a wider display, while opting for vertical mode for more conveniently.

PRODUCT SPEC SHEET

Wearable Armband Glove Scanner WT5524

ARMBAND PARAMETER

Armband Type	AB1800, AB2000, AB2200
Strap Length	Adjustable, 27cm and 38cm are available for AB2200
Armband Direction	360° rotatable
Applicable Screen Size	AB1800 for terminals with 4.0-6.5 inch screens AB2000 is suitable for screens of any size AB2200 for terminals with 4.7-7.2 inch screens
Armband Material	AB1800 - Silicone, PU, Webbing AB2000 - ABS, PU, Polyester AB2200 - PC, ABS, Webbing

SCANNER PHYSICAL PARAMETER

Scanner Dimensions	70.00mm(L) × 36.00mm(W) × 26.80mm(H)
Scanner Weight	37.5g (scanner body)
Notification	LED, Buzzer, Vibration

PERFORMANCE CHARACTERISTICS

Optical Resolution	2688 x 1520 pixels
Shutter	Global shutter
Sensor	2D CMOS Image
Skew, Pitch & Roll	Skew tolerance: ±60° from normal Pitch tolerance: ±60° from normal Roll tolerance: 360° from normal
Field of View	Horizontal 37°, Vertical 21.4°
Illumination	White LED
Aiming	Green Laser
Supported Symbolologies	1D: Code39, Code128, Codabar, Code11, UPC/EAN, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix 2 of 5, Korean 3 of 5, GS1 Databar, Code93, MSI, Composite 2D: PDF417, Postal CodesMicro PDF, Micro PDF417, Code128 Emulation, Aztec, Data Matrix, GS1 Data Matrix, QR Code, GS1 QR, Maxicode, Micro QR, Han Xin, Grid Matrix, DotCode, OCR

INTERFACE

USB Interface	USB Type-C
Coiled Cable	Both ends Type-C connector, 165mm
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

USER ENVIRONMENT

Ambient Light	Max 107,639 lux (direct sunlight)
Operating Temperature	14°F ~ 122°F / -10°C~50°C
Storage Temperature	14°F ~ 122°F / -10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M with frequency of 10 times per minutes.
Electrostatic Discharge (ESD)	±8kv dc discharge, ±15kv air discharge
Certificates	RoHS, NOM, EAC

DECODE RANGES

3 mil Code 39	2.7in. - 16.2in. /69mm - 411 mm
5 mil Code 39	2.5in. - 26.6in. /64mm - 676mm
5 mil PDF417	2.8in. - 19.6in. /71mm - 498 mm
6.67 mil PDF417	2.6in. - 25.6in. /66mm - 650mm
10 mil DataMatrix	2.2in. - 27.1in. /56mm - 688 mm
100% UPCA	2.5in. - 70.1in. /64mm - 1800 mm
15mil Code 128	2.6in. - 94.5in. /65mm - 2400mm
20mil Code 39	3.9in. - 130in. /100mm - 3300 mm
55 mil Code 39	8.5in. - 153.5in. /215mm - 3900 mm
100 mil Code 39	16.1in. - 165.3in. /410mm - 4200 mm
100 mil DataMatrix	3.3in. - 283.5in. /85mm - 7200 mm



AB1800



AB2200



AB2200

GENERALSCAN

Generalscan Inc.

200 Buckelew Ave, Jamesburg,
NJ 08831, USA
+1 732 895 6821

Generalscan Electronics GmbH

Hochstraße 42, 52525
Heinsberg Germany
+49 1516 7161256

Generalscan LLC

Calle San Luis Potosi 51,
Roma Norte 06700,
Ciudad de México
+52 5552727861

GENERALSCAN ELEKTRONIK VE TEKNOLOJİ SAN. VE TİC. LTD. ŞTİ.

FSM Mah. Siir Sk. Relux Plaza No 10,
Ümraniye 34764,
İstanbul, Turkey
+90 542 478 5873