

GS R1523 Ruglove - MK2

Bluetooth Wearable Scanner

Comfortable Microfiber Glove

The glove of MK2 made of microfiber, which is soft but not easy to deform, and is scratch resistant with high tensile strength. Working in harsh environments is no longer a problem.

A Glove with the Feature of Easy-to-Clean and Many-Time-Clean

The MK2 glove is easy-to-clean mostly due to the easily washable and can be frequently washed microfiber material, which contributes more on improving the hygiene and preventing the spread of germs. Workers always have a clean glove even if this set of scanners is in all-day, every-day use.

Press Slightly with One Hand to Scan, Enhanced Working Efficiency Greatly

With a slight press, the glove wear well, and ready to scan. In this way, workers do not need training on how to use it any more. Working efficiency improved greatly by easy operating and instant set-up.

Warm White Illumination along with Red Cross Laser Aiming Enhanced Accuracy, Speed, and User Comfort

Warm white illumination reduces glare and reflection, making barcodes easier to read in bright or highly reflective environments. Red cross laser ensures precise targeting even in low-light or high-contrast conditions. In addition, cross laser provides a clear visual guide, helping users accurately align the scanner with the barcode, reducing misalignment errors and minimizes the need for multiple scan attempts. The combination of warm white illumination and red cross laser enhance the readability of low-contrast, faded, or damaged barcodes. What's important is the warm lighting is softer on the eyes, reducing eye strain for workers performing repetitive scanning tasks.



Maximum replaceable parts bring minimize downtime

The removable and swappable scanner body and battery minimize the entire time of reassembly process. Furthermore, the one-second swappable battery makes sure scanners have virtually no downtime. There is no need to worry about dead battery to influence your daily working any more.

ACCESSORIES



Glove MK2 + Trigger



Armband
AB1800



Bluetooth Dongle
GDR201



Battery Charger
Dual-slot GS GCR201



Battery charger
GS GCR202(eight-slot)/203(sixteen-slot)

PRODUCT SPEC SHEET

Wearable Barcode Scanner GS R1523

PHYSICAL PARAMETER

Dimensions	66.5mm(L) × 34.7mm(W) × 25.2mm(D)
Weight	27.0g(Scanner body)
Battery Capacity	600mAh
Charging	5V ÷ 1A
Charging Time	120min
Battery Life	18.5h(scan once in 5 seconds)
Notification	LED, Buzzer, Vibration

PERFORMANCE CHARACTERISTICS

Optical Resolution	640×480 pixels
Shutter	Global Shutter
Sensor	2D CMOS Image
Skew, Pitch & Roll	Skew tolerance: ±55° from normal Pitch tolerance: ±55° from normal Roll tolerance: 360° from normal
Illumination	Warm White LED
Aiming	Red Cross Laser
Supported	1D: Code 128(ISBT 128, AIM 128, GS1 128) , EAN-13, EAN-8,
Symbologies	UPCE0, UPCE1, UPC-A, ISBN, ISSN, Code11, Interleaved 2 of 5, Code39, Code93, Code32, Codabar, Matrix 2 of 5, Industrial 25, IATA25, MSI Plessey, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded, Plessey, Febraban, Composite 2D: QR Code, Micro QR, Data Matrix, PDF417, Micro PDF417, Aztec, Maxicode, Han Xin Code, Dotcode, Composite
Interface	USB, Bluetooth
Offline Mode	Support storage of 3839 EAN-13 barcodes

SOFTWARE SUPPORT

Generalscan Keyboard Pro, Generalscan SDK Demo, Generalscan OTA Tools, Generalscan iCode, G-Service

USB

USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

USER ENVIRONMENT

Ambient Light	Max 100000lux (direct sunlight)
Operating Temperature	-20°C~50°C
Storage Temperature	-40°C~70°C
Humidity	5% - 95% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M with frequency of 10 times per minute.
Electrostatic Discharge (ESD)	±8kv DC discharge, ±15kv air discharge
Certificates	CE, FCC, KC, TELEC, RoHS, ANATEL, NOM, EAC

BLUETOOTH

Bluetooth Protocol	HID Keyboard, SPP, and BLE
Bluetooth Range	Communication distance connected to mobile phone > 98.43ft/30m (without obstructions)
Bluetooth OTA	Bluetooth OTA

DECODE RANGES

13mil EAN-13	55.0 - 350.0MM
5mil Code 39	55.0 - 120.0MM
13mil Code128	55.0 - 350.0MM
15mil QR	25.0 - 230.0MM
10mil Data Matrix	45.0 - 150.0MM
6.67mil PDF417	55.0 - 145.0MM

GENERALSCAN

Generalscan Inc.

📍 200 Buckelew Ave, Jamesburg, NJ 08831, USA
☎ +1 732 895 6821

Generalscan Electronics GmbH

📍 Hochstraße 42, 52525 Heinsberg Germany
☎ +49 1516 7161256

Generalscan LLC

📍 Calle San Luis Potosi 51, Roma Norte 06700, Ciudad de México
☎ +52 5552727861

GENERALSCAN ELEKTRONIK VE TEKNOLOJİ SAN. VE TİC. LTD. ŞTİ.

📍 FSM Mah. Siir Sk. Relux Plaza No 10, Ümraniye 34764, İstanbul, Turkey
☎ +90 542 478 5873