

GS R1521 Ruglove - MK2 Bluetooth Wearable Scanner

Comfortable microfiber glove

The glove of MK2 made of microfiber, which is soft but not easy to deform, and is scratch resistant with high tensile strength. Working in harsh environments is no longer a problem.

A glove with the feature of easy-to-clean and many-time-clean

The MK2 glove is easy-to-clean mostly due to the easily washable and can be frequently washed microfiber material, which contributes more on improving the hygiene and preventing the spread of germs. Workers always have a clean glove even if this set of scanners is in all-day, every-day use.

Press slightly with one hand to scan, enhanced working efficiency greatly

With a slight press, the glove wear well, and ready to scan. In this way, workers do not need training on how to use it any more. Working efficiency improved greatly by easy operating and instant set-up.

Durable and Rugged for All-Day, Every-Day Use

GS R1521 is dual-tested for durability-drop and tumble. Multiple drop it on concrete from 4.9ft./1.5M, tumble it from 3.3ft./1M with frequency of 10 times per minutes for 20,000 times, GS R1521 is engineered for durability and uptime.

Triggers built for intensive scanning

The triggers are rated for millions of pressing — instead of the typical few hundred thousand trigger presses. It is obvious that the frequency of replacing triggers getting lower, and also the cost.

NFC paring saves at least half of the connection time

Using the NFC makes the Bluetooth connection more convenient and faster. User can simply tap the scanner with any NFC-enabled devices. No need to open the bluetooth settings to identify and select the device.

Maximum replaceable parts bring minimize downtime

The removable and swappable sanner body and battery minimize the entire time of reassembly process. Furthermore, the one-second swappable battery makes sure scanners have virtually no downtime. There is no need to worry about dead battery to influence your daily working any more.

ACCESSORIES



Glove MK2 + Trigger



Armband AB1800



Bluetooth Dongle



Battery Charger

Dual-slot GS GCR201 GS GCR202(eight-slot)/203(sixteen-slot)



Battery charger

PRODUCT SPEC SHEET

Wearable Barcode Scanner GS R1521

PHYSICAL PARAMETER

Scanner Dimensions	$66.5MM(L) \times 34.7MM(W) \times 25.2MM(D)$
Scanner Weight	25.8g (scan body)
Glove Dimensions	260(L)×120(W)×2.5(D)mm
Glove Weight	21.2g
Material of Glove	Microfiber
Battery Capacity	600mAh
Charging	5V1A
Charging Time	120min
Battery Life	19.5 hours (scan every 5 seconds)
Notification	LED, Buzzer, Vibration

PERFORMANCE CHARACTERISTICS

Optical Resolution	640×480
Shutter	Global Shutter
Sensor	2D CMOS Image
Skew, Pitch & Roll	Skew tolerance: ±55° from normal
	Pitch tolerance: ±55° from normal
	Roll tolerance: 360° from normal
Illumination	White LED
Aiming	Red LED
Supported	1D: Code 128 (ISBT 128, AIM 128, GS1 128) , EAN-13,
Symbologies	EAN-8、UPC-E、UPC-A、ISBN、ISSN、Code11、
	Interleaved 2 of 5, Code39, Code93, Code32,
	Codabar、Matrix 2 of 5、Industrial 25、IATA25、MSI
	Plessey、GS1 DataBar、Plessey、Febraban
	2D: QR Code、Micro QR、Data Matrix、PDF417、Micro PDF417、
	Aztec, Maxicode, Hanxin, Dotcode, Composite
Interface	USB, Bluetooth
Offline Mode	Support storage of 3839 EAN-13 barcodes

BLUETOOTH

HID Keyboard, SPP, and BLE
Communication distance connected to mobile phone $>$
164.04ft./50m (without obstructions)
Bluetooth OTA

TRIGGER METHOD

Trigger	By the key on glove surface
riiggoi	by the key on glove surface

USB	
USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

USER ENVIRONMENT

Ambient Light	Max 100000lux (direct sunlight)
Operating Temperature	-10°C~50°C
Storage Temperature	-10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M
	with frequency of 10 times per minutes.
IP Level of Glove	Washable
Electrostatic	±8kv DC discharge, ±15kv air discharge
Discharge (ESD)	
Certificates	CE, FCC, KC, TELEC, RoHS, ANATEL, NOM, EAC

SOFTWARE SUPPORT

Generalscan Keyboard Pro, Generalscan SDK Demo, Generalscan OTA Tools, Generalscan iCode, G-Service

DECODE RANGES

13 mil EAN-13	50 - 325MM
5 mil Code 39	55 - 135 MM
13 mil Code128	50 - 330MM
15 mil QR	30 - 190 MM
10milData Matrix	40 - 130 MM
6.67 mil PDF417	50 - 135MM

GENERALSCAN

Generalscan Inc.

200 Buckelew Ave, Jamesburg, NJ 08831, USA

+1 732 895 6821

Generalscan Electronics GmbH

- (P) Hochstraße 42, 52525 Heinsberg Germany
- +49 1516 7161256

Generalscan LLC

- Calle San Luis Potosi 51, Roma Norte 06700, Ciudad de México
- +52 5552727861

GENERALSCAN ELEKTRONIK VE TEKNOLOJI SAN. VE TIC. LTD. ŞTİ.

- FSM Mah. Siir Sk. Relux Plaza No 10, Ümraniye 34764, Istanbul, Turkey
- +90 542 478 5873